

Defender 76LS Lift + Slide Door		
	MIN PANEL WIDTH: 30.5 in.	MAX PANEL WIDTH: 90 in.
	MIN HEIGHT: 52.2 in.	MAX HEIGHT: 102.4 in.
CONFIGURATION	Minimum Overall Width	Maximum Overall Width
XO, OX, XX_L, XX_R	61 in.	180 in. (NAFS tested to 144 in.)
OFF CENTER XO or OX	90 in.	
OXO, XOX		
OXXO	116 in.	

Defender 88LS Lift + Slide Door		
	MIN PANEL WIDTH: 30.5 in.	MAX PANEL WIDTH: 127.50 in.
	MIN HEIGHT: 71 in.	MAX HEIGHT: 120 in.
CONFIGURATION	Minimum Overall Width	Maximum Overall Width
XO, OX, XX_L, XX_R	61 in.	255.9 in.*
OFF CENTER XO or OX	120 in.	
OXO, XOX		
OXXO	144"	
*OX & XO configuration NAFS tested to 144 in.; OXO, XOX and OXXO tested to 255.9 in.		

All doors feature a softclose function for safety.

Double sided handles are recommended in high-traffic use, for very large (heavy) doors, or to improve accessibility.

Double sided handles limit the clear opening width.

Gear damper to reduce "flick" of handle is applied when the sash weight exceeds 200kg.

Notes

All size limitations refer to multiple panels unless otherwise noted.

All dimensions are heel dimensions.

*All maximums tested for NAFS compliance unless otherwise noted; engineering letter may be required for all doors that exceed the maximum NAFS tested size.